

### 24" Military Console Mount Monitor



#### Specification

##### Input Interface :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-D
- HDMI : 1 x HDMI (Optional)
- Video : 1 x AV (BNC connector)
- COM : 1 x RS232 for touch or remote control
- Power Input : 1 x DC input (D38999 connector)

##### Power Specification:

- Power Adapter : N/A
- Consumption : 70 W typical, normal operation
- Input : 9~36V DC Input
- Power Cord : N/A

##### Environment Tolerance:

- Operating Temperature : -10 deg. C to 55 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C

##### Touch Screen:

- Touch Screen : 5-wire resistive touch (optional)  
SAW touch (optional)  
P-Cap touch (optional)

##### Panel Specification :

- Size/ Type : 24" LCD (LED backlight)
- Active Area (mm) : 518.4 (H) x 324.0 (V)
- Pixel Pitch (mm) : 0.27675 (H)x 0.27675 (V)
- Resolution : 1920 x 1200 @ 60Hz
- Contrast Ratio : 1400 : 1 (typ.)
- Max. Colors : 16.7M colors
- Brightness : 400 nits (cd/m<sup>2</sup>)
- Viewing Angle : 176 (H); 176 (V)
- Response Time : 11/9 (typ.) (Tr/Td)
- Glass : EMI AR glass

##### OSD :

- OSD Input : 5 -key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

##### Order Information :

- Glass : AR glass protection (optional)
- Speaker : 2W Speaker x2 (optional)
- High Brightness : 1000 nits (optional)

#### Drawings

