

10.4" Military Multi-Functional Display

SDRML10D-FNV



Specification

System Features:

- **Features** : Sunlight Readable With MIL-C-675C
- **Panel Protection** : Vandal Proof Glass
- **Control Buttons** : 21-Key Programming Buttons
- **DNRS** : Applicable to DNRS228 System

Environment Tolerance:

- **Operating Temperature** : -30 deg. C to 60 deg. C
- **Storage Temperature** : -40 deg. C to 70 deg. C
- **Humidity** : 10 to 95% (Non Condensing)
- **Shock** : MIL-STD-810G Method 516.6
- **Vibration** : MIL-STD-810G Method 514.6C-3
- **Humidity** : MIL-STD-810G Method 507.5-7
- **High Temperature** : MIL-STD-810G Method 501.5-II
- **Low Temperature** : MIL-STD-810G Method 502.5
- **EMC** : MIL-STD-461F, RE102,RS103,CE101,CE102 CS101,CS114,CS115,CS116

Panel Specification :

- **Size/ Type** : 10.4" LCD
- **Resolution** : 800 x 600
- **Brightness** : 1000 (typ.)
- **Contract Ratio** : 550 : 1 (typ.)
- **Max. Colors** : 16.2M (8 bits/color)
- **Viewing Angle** : -80~ 80 (H); -80~ 60 (V)
- **Active Area** : 211.2 (H) x 158.4 (V)

Input/Output :

- **DVI** : 1 x DVI-I Input
- **HDMI** : 1 x HDMI Input
- **Video** : 1 x Video , CCIR/PAL/NTSC/RS-170/RGB
- **COM** : 1 x RS232 for BIST(Built-In Self-Test)
- **Power** : 1 x DC 13~36V Input

Dimensions:

- **Dimensions** : 250 x 194 x 84 mm
- **Weight** : 3200g

Drawings

